	ZGE-CI-Z-100-215
Basic	
Configuration	IP240S
Number of Pack	15
Short-circuit current	12.2kA
Electrical	
Rated charging Current	140A
Max. Charging Current	160A lasts 1minute
Nominal Capacity	
Voltage Range	600~876V
Nominal Voltage	768V
Max. continuous current	160A
Rated Power	100kW(0.5P)
Auxiliary Power	
Cooling Unit Power	Cooling:3.1KW;Heating:2.0KW
Voltage range	176-264V
BMS Power	60W
System	
Anticorossion	C5
IP rating	Battery:IP66,Control:IP55,NEMA 3R
Power connection	Fast Plug
Grounding Mode	⩽ 4Ω, Meet the Local Scope Requirements
Cooling Mode	Air Cooling
Storage Environment Temperature	-30~60 °C
Operating Environment Temperature	-25 ~55 °C
Environment Humidity	RH⩽95%（Non-Condensing）
Altitude Requirements	＜4000m(＞3000m Derating)
Dimension	1500*1400*2550mm
Weight	2800kg
Color	RAL7035
PCS	
DC side	
Rated Voltage	
Rated Current	
Max. Long-Term Operating Current	
Voltage Range	
Frequency	
Total Current Harmonics	
Wiring method	
Communications Interface	
Communications Protocol	
Certificate	IEC62477 IEC61000 CEI-016 VDE4110 EN50549 IEEE1547.1 UL1741 IEC62619 UL1973 UL9540A

ZHIGUANG